

GUARD TOUR SYSTEM



Spécifications

Dimension:

Height : 144mm

Width : 47mm

Thickness: 30mm

Weight : 200g

Color Blue

IP Rate IP67

Operating Temperature -40°C~+85°C

Reading Mode RFID 125 KHz
Reading distance 3cm -5cm

Communication USB, (CP2102, USB2.0) upload data 15000 pieces per min

Battery	<p>rated voltage : 3.7V</p> <p>rated capacity : 880Amh</p> <p>Dimension : 33mm × 25 mm×10 mm</p>
Standby time	<p>1、 Read tags per second, can be used at least 40 hours.</p> <p>2、 500 readings per day, can be used for 29 days. Five days for low power.</p>
Data Storage	16Mbit flash, 60,000 pieces
Prompt	Vibration with Colorful LED light. Red, Green, Blue, White.
Tag ID number	<p>1.8 bit Hexadecimal number in reader (4 byte), and 10 bit decimalism number in the software.</p> <p>2.Can be expanded to 10 bit Hexadecimal number (5 byte).</p>

Tags

Guard ID tag		36mm*28mm*6mm	3.8g
Round checkpoint tag		Φ30mm*4mm	2.8g
Cylinder Glass Tag		Φ6.6mm×27.7 mm	1.7g
Noctilucent checkpoint		76mm*56mm*10mm	19g
Orange Checkpoint		76mm*56mm*10mm	19g
Event Wallet			